

## C-Bus 12-Channel Relay, DIN Rail Series



L5112RVF Series

The L5112RVF Series units are C-Bus relay-switching devices designed to be mounted in electrical switchboards or similar enclosures. For ease of installation, they are DIN rail mounted, measuring 12 DIN modules wide. Twelve independent voltage free relay contacts are provided for general switching applications

The units include all C-Bus Learning features, which allow the units to be programmed without the need for a PC connected to the system. Alternatively, units can be programmed via a PC and the C-Bus Installation software.

The Series includes units complete with a0A rates relays for resistive, inductive or fluorescent loads.

The units consume no current from the C-Bus network during normal operation. The Series includes units available both with and without a 200mA C-Bus power supply for powering other C-Bus devices connected to the network (e.g., C-Bus Key Input Switches, Touchscreens, PIR detectors, e.t.c)

C-Bus connections are conveniently achieved at the unit through the use of RJ45 connectors, allowing similar units to be quickly looped together.

This Series of C-Bus units is capable of generating C-Bus clock signal and providing a C-Bus network burden. Both the clock signal and the burden are selectable through the C-Bus Installation Software.

Local toggle buttons are included to allow individual channels to be toggled at each unit, as well as via C-Bus commands. Remote On and OFF facilities are available, permitting all channels to be turned ON and OFF without C-Bus network communication.

The unit optically isolates the mains power from the safe extra low voltage C-Bus network. LED Indicators are provided to show the status of the C-Bus Network and the status of the unit.

Like all the other units that make up a C-Bus system, the DIN rail C-Bus units are Australian designed, developed and manufactured by Clipsal Integrated Systems Pty Ltd.

[clipsal.com/cis](http://clipsal.com/cis)

## L5112RVF C-Bus Professional Series Dimmer

- Provides twelve independent voltage free relay contacts in an 12M wide DIN rail enclosure
- Units available with 10A rated relays (resistive, inductive or fluorescent loads) and separate units with relays rated at 10A resistive and 1A fluorescent
- Units available both with and without 200mA C-Bus power supply on-board
- Up to 100 units without power supply 10 units with power supply are permitted on any one single C-Bus network (255 networks available in a C-Bus installation)
- Configured via either the C-Bus Installation Software or via the Learn Enabled Features
- Local ON/OFF toggle buttons allow individual channels to be manually overridden at each unit
- Remote On and OFF facilities permit all channels to be turned ON or OFF without C-Bus network communication
- The C-Bus side and output stages are electronically isolated
- Incorporates C-Bus Network Status, Mains Power Status and Load Status indicators
- Capable of generating a C-Bus clock signal if enabled
- A network burden is incorporated and is software selectable
- Logic states (and/or) configurable via installation software
- Relay interlocking feature selectable via installation software
- Incorporates power recovery options to restore loads 'as was', 'off' or 'on'
- 2 x RJ45 sockets are incorporated to facilitate the C-Bus connection
- Supplied with a 300mm C-Bus Category 5 patch lead complete with pre-terminated RJ45 connectors
- The output terminals accommodate 2 x 1.5mm<sup>2</sup> or 1 x 4.0mm<sup>2</sup> cable
- EMC Complaint to meet the requirements for marking with the CE and RCM marks
- Incorporate magnetically latching relays
- Capable of being programmed via the installation software without the need for a mains connection
- Draws 18mA when being programmed and no mains connection is made
- When a mains connection is made, then the unit does not draw any current from C-Bus
- Dimensions: W=215mm, H=85mm, D=65mm
- Weight: 600g.

### Product of Clipsal Australia Pty. Ltd.

A member of the Schneider Electric Group.



#### Head Office

12 Park Terrace, Bowden  
South Australia 5007  
PO Box 103 Hindmarsh  
South Australia 5007

Telephone +61 8 8345 9500  
Facsimile +61 8 8346 0845  
Internet www.clipsal.com/cis  
E-Mail cis@clipsal.com.au

**CIS Technical Support Hotline:**  
1300 722 247

**Customer Service Enquiries:**  
**1300 2025 25**

**National Customer Service Facsimile:**  
**1300 2025 56**

#### International Enquiries

##### International Sales and Marketing

Telephone +61 8 8269 0587  
Facsimile +61 8 8340 7350  
E-Mail export@clipsal.com.au

##### New Zealand

Clipsal Industries (NZ) Ltd  
Telephone +64 9 576 3403

##### Malaysia

Clipsal Integrated Systems (M) Sdn Bhd  
Telephone +60 3 7665 3555

##### Singapore

Clipsal Integrated Systems Pte Ltd  
Telephone +65 6415 3232/3233

##### China

Clipsal China Limited  
Telephone +86 755 8237 5959

##### Greece

Schneider Electric AE  
Telephone +30 69 4646 3200

##### Hong Kong

Clipsal Integrated Systems (HK) Limited  
Telephone +852 2487 0261

##### India

Schneider Electric India Pvt Ltd  
Telephone +91 11 5159 0000

##### Indonesia

PT Clipsal Graha Nusa  
Telephone +62 21 630 6430

##### Korea

Clipsal Korea Co. Ltd  
Telephone +82 549 5550

##### Pakistan

Clipsal Pakistan (Pvt) Ltd  
Telephone +92 21 506 7278

##### Philippines

Clipsal Philippines Inc.  
Telephone +632 683 0275-78

##### South Africa

Clipsal South Africa (Pty) Ltd  
Telephone +27 11 314 5200

##### Taiwan

Clipsal (Taiwan) Co Ltd  
Telephone +886 2 2558 3456

##### Thailand

Clipsal Thailand Ltd  
Telephone +66 2 952 5338-42

##### United Arab Emirates

Clipsal Middle East  
Telephone +971 6 5570 777

##### United Kingdom

Clipsal Integrated Systems  
C/o Schneider Electric  
Telephone +44 870 608 8 608

##### Vietnam

Clipsal - VTEC  
Telephone +848 856 3002



Clipsal Australia Pty Ltd reserves the right to change specifications, modify designs and discontinue items without incurring obligation and whilst every effort is made to ensure that descriptions, specifications and other information in this catalogue are correct, no warranty is given in respect thereof and the company shall not be liable for any error therein.

© Clipsal Australia Pty Ltd.

The identified trademarks and copyrights are the property of Clipsal Australia Pty Ltd unless otherwise noted.