



LINN

KEY FEATURES INCLUDE

- Linn's flagship pre-amplifier, combining technological and aesthetic excellence with pitch accurate sound quality
- Cool running, sleek case machined from solid aluminium that isolates and screens the circuitry
- Short, simple audio signal path designed to optimise the purity and accuracy of reproduction
- Three line level inputs, one balanced input
- Three line level outputs, one balanced output
- Compatible with Linn KNEKT multi-room system

The KLIMAX KONTROL pre-amplifier is a high performance audio component designed to complement KLIMAX power amplification both sonically and aesthetically.

The machined-from-solid clamshell construction of the KLIMAX casework is a beautiful and unique design that screens, protects and stabilises the internal electronics.

Inside there are four circuit boards, one an auto ranging slimline power supply providing silent power to the unique audio circuit board. The display and control boards are separated from the audio board to keep the audio signal path as clean as possible. This complete product gives unsurpassed performance from a compact audio component.

KLIMAX KONTROL PRE-AMPLIFIER

SPECIFICATION

The ultimate reference quality stereo pre-amplifier



KLIMAX KONTROL PRE-AMPLIFIER

TECHNICAL SPECIFICATION

The ultimate reference quality stereo pre-amplifier

■	Introduced	2002
■	Type	Reference quality pre-amplifier
■	Input connectors	Unbalanced: 3 sets WBT Phono sockets Balanced: 1 set Female XLR Pin connections: Phono-inner hot, outer hot XLR- Pin 1: OV, Pin 2: Hot, Pin 3: Cold
■	Output connectors	Balanced: 1 set XLR Unbalanced: 1 set WBT Phono sockets
■	Fuse rating	T 800 mA anti-surge
■	Mains supply range	100 V - 240 Vac nominal
■	Audio inputs	Impedance (unbalanced) 10 k Ω Signal (unbalanced) 0 dBV (nominal) Impedance (balanced) 7.8 k Ω
■	Audio outputs	Impedance (unbalanced) 300 Ω Impedance (balanced) 600 Ω
■	Gain range	Minimum to maximum -95.5 dB to +9.5 dB in 0.5 dB steps
■	Frequency response	2.3 Hz - 200 kHz
■	Distortion (harmonic)	0.0025% (1 kHz @ 0 dBV)
■	Dynamic range	115 dB
■	Cross talk	Channel to channel -116 dBV Source to source -116 dBV
■	Power consumption	15 W
■	Dimensions	W 350 mm x D 355 mm x H 60 mm W 13.8 inches x D 13.9 inches x H 2.3 inches
■	Weight	9 kg / 19.84 lbs

The above information is subject to change without prior notice

Linn Products Ltd

Floors Road, Waterfoot, Glasgow G76 0EP, Scotland, UK.

Telephone: +44 (0) 141 307 7777, Facsimile: +44 (0) 141 644 4262, Helpline: 0500 888909, E-mail: helpline@linn.co.uk, Website: www.linn.co.uk

Linn Products Inc

8787 Perimeter Park Boulevard, Jacksonville FL 32216, USA.

Telephone: +1 (904) 645 5242, Facsimile: +1 (904) 645 7275, Helpline: 888-671-LINN, E-mail: helpline@linninc.com, Website: www.linninc.com

Linn Deutschland GmbH

Albert-Einstein-Ring 19, 22761 Hamburg, Deutschland.

Telephone: +49 (0) 40-890 660-0, Facsimile: +49 (0) 40-890 660-29, E-mail: info@linngmbh.de, Website: www.linn.co.uk

Linn Records Ltd

Floors Road, Waterfoot, Glasgow G76 0EP, Scotland, UK.

Telephone: +44 (0) 141 303 5027, Facsimile: +44 (0) 141 303 5007, Helpline/Mail order: +44 (0) 141 303 5029, E-mail: records@linn.co.uk, Website: www.linnrecords.com

© 2003, Linn Products Limited. All rights reserved.

Linn, the Linn logo and KLIMAX are trade marks of Linn Products Limited, registered in at least the UK and/or EU.

Pack 659 (Revised 01/04)